

iBridge C5x N5-X25 Antenna


Incredible RF Performance

ANTENNA SPECIFICATIONS

- Gain: 25 dBi
- Polarization: Dual-slant 45°
- Beamwidth, Symmetric (3 dB): 8°
- Front-to-Back Ratio (min): 40 dB
- Front-to-Side Ratio (min): > 45 dB
- Weight: 0.98 kg (2.15 lbs)
- Dimensions: Diameter: 429 mm (16.89") Depth: 116 mm (4.57")
- Mount: Mimoso N5-X, twist on
- Wind Survivability: 200 km/h (125 mph)
- Wind Loading: 36.26 kg @ 160 km/h (79.95 lbs @ 100 mph)

ENVIRONMENTAL

- Outdoor Ingress Protection Rating: IP55
- Operating Temperature: -40°C to +55°C (-40°F to 131°F)
- Operating Humidity: 5 to 100% condensing
- Operating Altitude: 4,420 m (14,500') max
- Shock & Vibration: ETS 300-019-2-4 class 4M5



iBridge C5x N5-X25 Antenna

The N5-X25 antenna, paired with a C5x, is an ultra-rugged solution that provides extended frequency operation from 4.9–6.4 GHz, with best-in-class noise immunity.

Delivering the ultimate in flexibility and value, the N5-X25 is the go-to solution for 5 GHz point-to-point, or point-to-multipoint deployments.